TECHNICAL SPECIFICATION

SPARX

SPARX B

Ultralight, personalised active wheelchair with a box frame.

CONSTRUCTION AND EQUIPMENT

01 · FRAME AND CONSTRUCTION

Frame type
Box (closed)

Frame material
Aluminium tube, ∅ 22 mm

Weight
8 kg total / 5 kg without wheels *

Geometry
7 made-to-measure parameters

Camber
2° rear wheel camber

Side guards
Aluminium – black or frame colour

02 · STANDARD EQUIPMENT

Upholstery
3D Sonic

Brakes
Aluminium

Rear wheels
24″

Front castors
4″ or 5″, aluminium

Footrest
Tube or plate

Hand rims
Standard

03 · ADDITIONAL OPTIONS

Hand rims
Tetra (rubber)

FRAME COLOURS

Black Grey Silver Red Brown Olive

3D SONIC UPHOLSTERY



Black Grey Blue Red Rust Olive

FOOTRESTS

Plate footrest

Tube footrest

* Weights are nominal and vary with the selected configuration.

SPARX

SPARX B

7 made-to-measure parameters, set per order.

ADJUSTMENT RANGES



01 SEAT WIDTH

25–45 cm · every 1 cm

02 SEAT DEPTH

25–45 cm · every 1 cm

03 BACKREST HEIGHT

20–40 cm · every 5 cm

04 FRONT FRAME HEIGHT

38–52 cm · every 1 cm

05 REAR FRAME HEIGHT

38–50 cm · every 1 cm

06 FRAME LENGTH

30–62 cm · every 1 cm

07 CENTRE OF GRAVITY

2–12 cm · every 1 cm

SPARX SP. Z O.O.
Rondo Daszyńskiego 1, Warsaw, Poland
info@sparxmobility.com www.sparxmobility.com

* Production time up to 60 days. * Registered in EUDAMED (EU).